




# HIRSCHMANN

A BELDEN BRAND

## Product information MAS 50 S grau/grey

Industrial Connecting Solutions: Circular Connectors: Audio/Video Connectors: DIN EN 60 130-09 Connectors (MAS/MAK series): without locking screw: Straight plugs: MAS 50 S grau/grey

<http://e-catalog.hirschmann.com/link/57078-24228-256281-256282-24384-24385-24387-34400/en/conf/uistate>

Name	MAS 50 S grau/grey
	
	plug with insulated handle; solder joint
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Type	MAS 50 S grau/grey
Order No.	930 131-517
Type of contact	male
Description	plug with insulated handle; solder joint
Housing Color	grey
Number of contacts	5
Conductor size	$\leq 0.34 \text{ mm}^2$
<b>Technical data</b>	
LF output "Phone"	EN 60 130-09
Pole arrangement DIN	DIN 41 524
Rated current	4 A
Rated voltage	AC/DC 34 V
Cable diameter	5.5 mm
Type of termination	solder
<b>Material</b>	
Contact material	brass
Contact surface material	tin plated
Contact bearer material	PA 66/UL standard 94V-2
Housing material	PE
<b>Environmental conditions</b>	
Protection class (IEC 60529)	IP 30
Temperature range	-20 °C to +60 °C
<b>Scope of delivery and accessories</b>	
Packaging	retail package, polyethylene bag



# HIRSCHMANN


A Belden Brand

Industrial Connecting Solutions: Circular Connectors: Audio/Video Connectors: DIN EN 60 130-09 Connectors (MAS/MAK series): without locking screw: Straight plugs: MAS 50 S grau/grey

<http://e-catalog.hirschmann.com/link/57078-24228-256281-256282-24384-24385-24387-34400/en/conf/ui/state>

## Picture

### Drawing



## Belden Deutschland GmbH

Im Gewerbepark 2  
58579 Schalksmühle  
Germany  
Phone: +49 7127/14-1806  
E-Mail: [icos-sales@belden.com](mailto:icos-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.